

BRB / BRB-AA RESINATOR

Resin-Bonded Specialty Bags

- ▶ INKS
- ▶ PAINTS
- ▶ COATINGS
- ▶ HYDRAULIC FLUIDS
- ▶ RESINS
- ▶ ADHESIVES
- ▶ PRODUCED FLUIDS
- ▶ PETROLEUM PRODUCTS

ORDER GUIDE



Once again, The Strainrite Companies delivers true filtration innovation by combining only the positive qualities of resin-bonded cartridges with the proven advantages of a Strainrite premium quality filter bag.

Resinator users gain the non-compressible media depth of a resin filter, along with the greatly enhanced solids loading capacity and cost saving features of a Strainrite gradient-density filter bag. This product excels in a wide variety of high viscosity fluid filtration applications where authoritative removal of problematic gels is required.

These "hard body" filter bags represent a significant advancement in the utilization of rigid fiber technology and illustrate the leadership role The Strainrite Companies plays in supplying vision and technical leadership when designing and manufacturing liquid filter bags.

This graduated double layer product design combines the depth loading efficiency of resin bonded cartridges with the greater dirt loading capacity of a filter bag creating the most cost effective method for filtering both low and high viscosity fluids.



New: Resinator filter bags are now available in an AA (added area) configuration. This configuration provides 70% more surface area and often provides a disproportionately larger benefit. A Resinator filter bag in the AA configuration combines the benefits of a non-compressible filter medium and the extended filter life and greater throughputs of added surface area. (Requires use of an AA basket.)



- ▶ NON-COMPRESSIBLE MEDIA DEPTH
- ▶ RIGID FIBER TECHNOLOGY
- ▶ GRADUATED DOUBLE LAYER
- ▶ HIGH DIRT LOADING CAPACITY

** note: for AA bags that will not be placed in a Strainrite-manufactured AA basket, or that will be used with a basket-insert, a non-standard length bag may be required. Contact your Strainrite distributor for assistance.

MAXIMUM OPERATING TEMPERATURE	
180°F (80°C)	with polypropylene hardware
250°F (121°C)	with polyester hardware or metal ring

ORDER OPTIONS

MATERIAL	
BRB	Resin-Bonded Polyester Felt
MICRON RATINGS	
1T, 1, 5, 10, 25, 50, 75, 100, 200	
FINISH	
P	Plain
SIZE	
1	7" x 16"
2	7" x 30.5"
RING	
P	Polypropylene P-Flange
M	Polypropylene M-Flange
PER	Polyester P-Flange
MER	Polyester M-Flange
SHS	Carbon Steel Ring w/ Handle Strap*
SSHS	Stainless Steel Ring w/ Handle Strap*
PRHS	Polypropylene Ring w/ Handle Strap*
<small>*Not available for AA bags</small>	
OPTIONS	
-	Double Layer Standard Bag
SL	Single Layer Standard Bag
SLAA	Single Layer Added Area Bag